

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61C 1/02, 1/16	A1	(11) International Publication Number: WO 95/15127 (43) International Publication Date: 8 June 1995 (08.06.95)
(21) International Application Number: PCT/US94/03799 (22) International Filing Date: 7 April 1994 (07.04.94) (30) Priority Data: 08/162,682 3 December 1993 (03.12.93) US (71) Applicant: GULL LABORATORIES, INC. [US/US]; 1011 East 4800 South, Salt Lake City, UT 84117 (US). (72) Inventor: FIFE, Richard, K.; 1285 East Hemingway Drive, Salt Lake City, UT 84121 (US). (74) Agent: FOSTER, Lynn, G.; 602 East 300 South, Salt Lake City, UT 84102 (US).		(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: ANTI-MICROBIAL APPARATUS AND METHOD FOR DENTAL HANDPIECES



(57) Abstract

An anti-microbial apparatus (20) and methods are disclosed, which provide capacity to process a handpiece (112) between patients including soaking, de-overburdening by ultrasonic energy (at TR1), treating with anti-microbial heat (at 50), accommodating coordinated through separate autoclaving, and accommodating packaging in a heat shrunk sheath (71) to prevent contamination through the air. The distal portion (170) of the sheath (71) is initially removed along weakened paths (158, 164) to expose the head of the handpiece, accommodating grasping of the handle through the remainder of the sheath during use. After use, the remainder of the sheath (172) is removed along a weakened path (158) and discarded. The anti-microbial apparatus (20) comprises a casing (22) with one or more covers (26, 28). An ultrasonic basin (90) provides a bath for soaking, liquid anti-microbial activity and removal of debris. A heat chamber (50) accommodates manual introduction and movement of the distal end and a substantial portion of the handle of the handpiece to dry and expose the handpiece to anti-microbial heat and anti-contamination sheath upon the handpiece.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1-

ANTI-MICROBIAL APPARATUS AND METHOD FOR
DENTAL HANDPIECES

Technical Background

5 The present invention relates generally to dental
handpieces and more specifically to anti-microbial
apparatus and methods for treating dental handpieces.

Background Art

10 Prevention of contamination and cross-
contamination have long been matters of primary
concern in the dental/medical field. Where handpiece
instruments must be reused on successive patients care
is required as are certain anti-microbial steps to
prevent transmission of virally or bacterially caused
infections from one patient to another. An equal
15 concern is to obviate transmission of such infections
from or to the health care provider.

20 An increasing awareness of the potential for the
spread of highly contagious viral and bacterial
diseases has led to further emphasis being placed on
infection control in the dental operatory. The
American Dental Association (ADA) and the Centers for
Disease Control (CDC) have been instrumental in
publishing guidelines intended to reduce the
opportunity for disease transmission during the
25 practice of dentistry. These recommendations support
the use of protective apparel by dental professionals
whose ordinary duties require hands-on contact with
patient body fluids, instrumentation and materials
used in dental procedures. It is also recommended
30 that non-disposable instrumentation and materials used
in the dental operatory be at least disinfected.

"Sterilization" is the process by which micro-
organisms are destroyed, including viruses, bacteria,
fungi, and spores. Sterilization may be achieved by

-2-

(1) steam under pressure (autoclave), (2) prolonged dry heat, (3) chemical vapor, (4) ethylene oxide gas, and (5) submersion in chemical sterilants. "Disinfection" is less lethal to microbials than sterilization and typically requires application of a chemical registered with the EPA.

The ADA has recommended that high-quality disposable medical gloves, a surgical mask covering the nose and mouth, and protective eye wear be worn by dental professionals due to constant exposure to patient-contaminated coolant aerosols associated with high speed handpieces as well as exudates of blood, pus, saliva, oral tissue, and decayed tooth material. It is recommended that the dental assistant and the hygienist wear disposable medical gloves. Hand washing and use of oral rinses, a rubber dam, and a saliva evacuation system are also encouraged. Training each health care provider is also important.

The ADA has also recommended autoclaving for instruments and non-disposable materials that are able to withstand the high heat of an autoclave cycle. Non-autoclavable instrumentation and materials should be chemically disinfected with a properly diluted, and freshly prepared disinfectant solution according to the manufacturer's instructions. Large equipment in the dentists' office should be "wiped down" routinely with a suitable anti-microbial solution. Significantly, hepatitis B and HIV are heat sensitive viruses, which are essentially rendered non-contagious by short-term autoclaving.

Except for a suggestion of wiping the handpiece routinely with recommended "wipe down" disinfectants, there is, to our knowledge, no other ADA recommended technique for the disinfection of heat intolerant handpieces between patients. And yet, the handpiece

-3-

is subjected to the exact same patient-contaminated coolant aerosols and exudates as are the dentist's hands, nose and mouth, and eyes. The handpiece is not only subjected to the contaminated material cast onto it by the coolant aerosol and the mechanical rotation of the tool, but also contaminants transferred to the handpiece by the dentist's glove. Thus, a potential source of cross-contamination from patient to patient exists through the handpieces and microbial contaminants surviving the disinfectant wipe are likely to be transferred to subsequent patients on the newly-donned gloves of the dental professional. Handpieces in today's technology have turbine blades which spin at more or less 500,000 revolutions per minute under air pressure. When the air and/or water pressures are turned off, a vacuum is created which may suck blood, saliva, and serum into the handpiece as a potential source for cross-contamination.

Transmission of microbials through the air in dental offices is also a matter of substantial concern.

Diseases of concern comprise the common cold, hepatitis B (HBV), non-A/non-B hepatitis, influenza, measles (German and rubeola), tuberculosis, staphylococcus, and streptococcus, herpes infections including chicken pox, infectious mononucleosis, epstein bar, herpetic whitlow, herpetic conjunctivitis, and AIDS (the HIV [human immunodeficiency virus] virus).

While it is clear that autoclave sterilization is the anti-microbial treatment of choice, the cost of buying, operating, and maintaining autoclave equipment is high and more handpieces need to be purchased and utilized where handpiece autoclaving occurs between each patient. Also, as stated above, not all

-4-

handpieces can withstand the heat of autoclaving. Thus, many doctors today, however, appear to find it impractical to sterilize handpieces after each patient use because of possible damage to the devices and the
5 necessary burdensome financial investment in multiple handpieces required to maintain an acceptable instrument flow. Nevertheless, the CDC currently recommends heat treatment of all handpieces using also
10 acceptable methods which assure internal and external sterility between patients.

-5-

Disclosure of the Invention

In brief summary, the present invention is intended to alleviate the above-mentioned problems of the prior art. The present invention comprises a multiple stage anti-microbial apparatus and methods are provided which significantly address the contamination and cross-contamination problems mentioned above. The present invention provides the capacity to process a handpiece between patients including soaking, de-overburdening via use of ultrasonic energy, treating with exposing to anti-microbial heat, accommodating coordinated though separate autoclaving, and accommodating contiguously packaging in a heat shrunk sheath after multiple anti-microbial treatment to prevent later contamination through the air. The sheath may be manually severed and removed immediately prior to use on an ensuing patient. Preferably, only a distal portion of the sheath is initially removed along weakened path to expose the operative head of the handpiece, accommodating grasping of the handpiece handle through the remainder of the sheath during use of the handpiece on the patient. After such use, the remainder of the sheath is removed along a weakened path and discarded.

The apparatus is relatively inexpensive, but efficacious as a microbial deterrent. In its preferred form, the anti-microbial apparatus comprises a portable casing with one or more covers. An ultrasonic basin provides a bath for soaking, liquid anti-microbial activity and removal of debris. A heat chamber accommodates facile manual introduction and movement therein of the distal end and a substantial portion of the handle of the handpiece, following the bath treatment, to dry and expose the handpiece to

-6-

anti-microbial heat and anti-contamination sheath upon the handpiece. The preferred apparatus is without water or drain connections, depending only on household electricity and equipment found in the health care provider's office for operation.

With the foregoing in mind, it is a primary object of the present invention to provide a novel apparatus and method which alleviate the problems of the prior art mentioned above.

An additional important object of the present invention is the provision of a multiple stage anti-microbial apparatus and related methods which significantly address the contamination and cross-contamination problems mentioned above.

An additional significant object of the present invention is to provide a novel method and unique apparatus by which a handpiece may be processed between successive uses on different patients to include soaking, removal of over-burden through use of ultrasonic energy, exposure to anti-microbial liquid, drying, exposing to anti-microbial heat, accommodating coordinated though separate autoclaving, and accommodating contiguously packaging of the handpiece in a heat shrunk sheath after multiple anti-microbial treatment to prevent later contamination through the air.

It is a further dominant object to provide a sheath which is heat shrunk upon a handpiece following anti-microbial treatment which accommodates manual severing thereof and removal prior to use on another patient.

It is a further paramount object to provide a novel handpiece sheath accommodating heat shrinking upon the handpiece and removal thereafter of a distal portion of the sheath only at the time of subsequent

-7-

use along a weakened path to expose the operative head of the handpiece.

5 A further object of value is the provision of a heat shrinkable sheath with which a handpiece is encapsulated following anti-microbial treatment which accommodates grasping of the handpiece handle through a portion of the sheath during use of the handpiece and removal and discarding of the grasped portion of the sheath following use of the handpiece.

10 It is an additional object of the present invention to provide a novel anti-microbial apparatus which is relatively inexpensive, but efficacious.

15 An additional dominant object of the present invention is the provision of an anti-microbial apparatus which comprises a portable casing in which an ultrasonic basin and a heat chamber are carried.

20 A further principal object of the present invention is the provision of a novel anti-microbial apparatus comprising an ultrasonic basin which provides a bath for soaking, liquid anti-microbial activity, and removal of debris.

25 Another paramount object of the present invention is the provision of a novel anti-microbial apparatus comprising a heat chamber which accommodates facile manual introduction and movement therein of the distal end and a substantial portion of the handle of a handpiece following anti-microbial treatment.

30 An additional valuable object of the present invention is the provision of an anti-microbial apparatus comprising a heat chamber accommodating facile manual introduction and movement therein of the distal end and a substantial portion of the handle of a handpiece after the handpiece is placed in a heat shrinkable plastic to heat shrink the sheath as an
35 anti-contamination measure.

-8-

A further important object of the present invention is the provision of an anti-microbial apparatus which is without water and drain connections and operates using household electricity.

5 A further primary object of the present invention is to provide a novel anti-microbial apparatus and related methods for use on most hand held medical instruments including but not limited to dental handpieces.

10 These and other objects and features of the present invention will be apparent from the detailed description taken with reference to the accompanying drawings.

-9-

Brief Description of the Drawings

Figure 1 is a perspective representation of an anti-microbial apparatus embodying the principles of the present invention;

5 Figure 2 is an enlarged rear elevation of the anti-microbial apparatus of Figure 1 with an exhaust baffle removed for clarity of illustration;

10 Figure 3 is a side elevation of the anti-microbial apparatus of Figure 1, with the exhaust baffle in place;

Figure 4 is a perspective representation, partially exploded, of the anti-microbial apparatus of Figure 1 showing the two lid segments pivoted into open positions;

15 Figure 5 is an enlarged fragmentary perspective of the left portion of the anti-microbial apparatus of Figure 1, with the removable slotted lid positioned over the bath-forming basin of the apparatus;

20 Figure 6 is a bottom exploded perspective representation of the basin of Figure 5, removed from the remainder of the apparatus of Figure 1;

25 Figure 7 is an enlarged perspective representation of the anti-microbial apparatus of Figure 1 with the two covers open and the internal circuitry and heat conduits exposed to view;

Figure 8 is an enlarged perspective representation of the exhaust baffle shown to the right in Figure 3;

30 Figure 9 is a plan view of a heat shrinkable sheath for encapsulation of a handpiece following anti-microbial treatment;

Figure 10 is a perspective representation of a dental handpiece encapsulated by the sheath of Figure 9 after the sheath has been heat shrunk;

-10-

Figure 11 is a main wiring diagram for the anti-microbial apparatus of Figure 1;

Figure 12 illustrates a DC power circuit;

Figure 13 is a heat/blower control circuit
5 diagram;

Figure 14 is a diagram of an ultrasound timer circuit; and

Figure 15 is a diagram of an overheat control circuit.

-11-

Best Mode for Carrying Out the Invention

Reference is now made to the drawings, wherein like numerals are used to designate like parts throughout. Attention is particularly directed to
5 Figures 1 through 10 which illustrate one anti-microbial apparatus, generally designated 20, fashioned in accordance with the principles of the present invention.

Broadly, the present invention comprises a
10 portable device encased within a common housing, generally designated 22. Housing 22 comprises a one-piece base or receptacle, generally designated 24, formed of a satisfactory strong shape-retaining synthetic resinous material. The housing 22 comprises
15 two housing lids or covers, respectively generally designated 26 and 28. Each cover 26 and 28 is secured to the base 24 by a hinge, respectively generally designated 30 and 32 (Figure 2). The cabinet comprising the base 24 and covers 26 and 28 is of a
20 modified clamshell design, providing a compact, lightweight, and yet effective anti-microbial apparatus, the outside dimensions of which may comprise 12 inches from front-to-back, 13 inches from side-to-side, and 6-1/2 vertical inches. The base 24
25 and lids 26 and 28 are preferably thermo molded of durable, di-electric easy-to-clean, high stain-resistant ABS plastic.

Exposed beyond the base 24 is a rocker actuator for a master off/on main power switch SW1 (located at
30 one side of the base 24) and a panel 25 of membrane switches SW2, SW3, and SW4 for, respectively, enabling an ultrasonic circuit, generating anti-microbial heat at a heat applying site, and generating heat for heat shrinkage of sheath upon a handpiece following anti-
35 microbial treatment. At the rear of the base 24 are

-12-

reset buttons for circuit breakers 34 and 36 by which
five amp and 15 amp circuit breakers may be,
respectively, reset, as explained herein in greater
detail. An electrical socket 38 is adjacent to the
5 reset buttons for located circuit breakers 34 and 36.

The electrical receptacle 38 is a 112 volt 15
amp AC electrical receptacle.

As best seen in Figure 2, electrical socket 38
conventionally comprises three male connectors for
10 engagement with the female end of a conventional
electrical cord (not shown), the male end of which is
connected to a source of 110 volt AC electrical power,
such as is readily available in homes and commercial
buildings.

15 The base 24 and the two exterior covers 26 and 28
are shells and comprise a relatively thin wall. See,
for example, wall 40 illustrated in Figure 2. Wall 40
comprises the bottom wall portion of the base 24. A
plurality of apertures 42 are placed in the bottom
20 wall portion 40, only one of which is illustrated in
Figure 2, for the purpose of accommodating atmospheric
or ambient air flow through the base 24 to cool the
circuitry and other components of the apparatus 20
during use.

25 The base 24 is supported upon four conventional
elastomeric pedestals or non-slip feet 44, each of
which is adhesively secured at interface 46 to the
exterior surface 48 of the bottom wall 40. See
Figures 2 and 3. The lightweight construction of the
30 apparatus 20, including but not limited to the base 24
and covers 26 and 28, allow convenient portability,
independent of the size, strength, and gender of the
person assigned to move the apparatus 20 from place-
to-place.

-13-

The apparatus 20 comprises a continuously open heating chamber 50. Heating chamber 50 is defined by a glazed, ceramic tube 52, illustrated as comprising inside and outside diameters, respectively, of uniform size throughout the length of the tube 50. Thus, the uniform wall thickness of tube 52 is constant. The tube 52 comprises an entry opening 54 and an exit or exhaust opening 56. Exhaust opening 56 is best illustrated in Figure 2, where exhaust baffle 55 has been removed for clarity.

As shown in Figures 1, 4, and 7, the heating chamber tube 52 is in communication with the discharge end 58 of a hot air supply tube 60. As can be seen from Figure 4, heating chamber tube 52 and hot air supply tube 60 are disposed vertically below cover 28 when it is closed. A removable platform 66 is superimposed over tubes 52 and 60, as well as over the other interior components, particularly circuitry, disposed below the lid 28. The platform 66 is generally planar and comprises corner apertures through which screws 68 extend. The threads of screws 68 also engage, respectively, threaded apertures 70 in plastic brackets 72. See Figure 7. L-shaped brackets 72 are secured to the associated wall surface base 24 using a suitable adhesive or any other desired conventional form of attachment. By removing screws 68, the platform 66 may be lifted from base 24 to accommodate inspection of and repairs within the compartment 65 below the platform 66 within the base 24.

As can best be seen in Figure 7, the interior of the base 24 is compartmentized into two compartments by vertical wall 74, i.e., the above-described compartment 65 within the base 24 below platform 66 and a second compartment 76 directly below the

-14-

exterior lid or cover 26 when closed. The compartment 76 is largely hollow, for reasons yet to be explained, but accommodates switch SW1 and placement of fan or blower 78.

5 Compartment 76 is only partially closed by a platform 80 (Figure 4). Platform 80 is secured by removable screws 82 passing through corner apertures in the platform 80 into threaded bores 84 (Figure 7) in the upper horizontal leg of L-shaped brackets 86.
10 Each bracket 86 is secured to the associated interior surface of the wall comprising base 24 in any suitable fashion, such as by use of a suitable adhesive or bonding compound. Thus, platform 80 may be removed by unthreading screws 86 and, when removed, exposes the
15 compartment 76. See Figure 7.

 Platform 80 comprises a relatively large aperture, located, sized, and shaped to accommodate gravity recessed placement of a stainless steel basin, generally designated 90. The basin 90 has a rolled
20 peripheral edge 92 and a rectangularly-shaped tapered side wall 94 which merges with a flat bottom wall 96. The size and shape of basin 90 is selected so as to provide an appropriate liquid bath of predetermined acceptable volume for cleaning and anti-microbial
25 treatment of medical/dental handpieces, as explained hereinafter in greater detail. Since the basin 90 simply rests at lip 92 upon the top surface of platform 90, the basin 90 can be lifted, as desired, to accommodate removal of the platform 80 and/or
30 access to compartment 76. The basin or tank 90 may comprise a 16 or 22-gauge 302 stainless steel stamped and drawn tank comprising a width at lip 92 of 4-1/2 inches, a length at lip 92 of 8.375 inches, and a 3-inch depth. The tank 90 is designed to operate with

-15-

one liter of cleaning/disinfecting solution filled to an inscribed line 95 (Figure 4).

As best illustrated in Figure 6, the stainless steel basin 90 is grounded at terminal 98 (Figure 6), which is located in electrical communication with a side wall 94 of the basin 90 by soldering and pliant anchors 100. An ultrasonic transducer TR1 is yieldingly secured to the bottom 96 of the basin 90. While any suitable form of attachment may be used, the attachments 99 and 100 illustrated in Figure 6 may comprise baked-on epoxy and silicone rubber, respectively.

A transparent, removable plastic basin lid 102 is selectively positioned, as illustrated in Figure 5, over a liquid bath placed in basin 90, for purposes yet to be explained. The plastic lid 102 is substantially rectangular in its configuration, but slightly smaller dimensionally than the size of lip 92 of the basin 90 thereby accommodating interior or recessed placement, as illustrated in Figure 5.

The plastic lid 102 comprises a knob 104 for manually manipulating the basin lid 102. Knob 104 is secured, as by bonding, gluing, or in any other suitable way at site 106 to or at the top surface 108 of basin lid 102. Basin lid 102 is illustrated as being substantially planar and of uniform thickness throughout. The perimeter comprises three edge slots 110, accommodating passage therethrough and upward extension therefrom of the proximal end of up to three handpieces 112, at any point in time, with the distal end and part of the handle of each such handpiece disposed within the bath of the basin 90, as illustrated in Figure 5.

As best illustrated in Figure 4, platform 66 accommodates placement of a stack or supply of paper

-16-

5 towels 67. Adjacent thereto is a recess or well 69 into which a supply of handpiece heat shrinkage sheaths, each generally designated 71, is placed for periodic use, as hereinafter explained in greater detail.

10 Apparatus 20 is preferably lightweight, low cost, and easily operated with limited technical training by any health care provider, including technicians, nurses, doctors, and aids as well as dentists and doctors. Apparatus 20 is unconnected, except for electrical power in the illustrated embodiment, although the present invention contemplates a breadth such that a portable electrical power supply and liquid connections could be used. No drains and no
15 water connections are involved in the illustrated embodiment.

20 The ceramic oven comprising tube 52 is small and always open accommodating a single hand held instrument. Flow therethrough from hot air supply tube 60 is laminar, the fan or blower 78 (Figure 7) drawing air into the base 24 through holes 42, through influent fan or blower ports 79 across heat coils disposed in tube 60, into heating chamber tube 52. Blower 78 may be a motor and fan in combination and
25 may be a Mabuchi RS285SA, 2073 DC motor connected to a medium pressure fan.

30 A second continuously running fan is preferably positioned below juncture 61 to exhaust hot air accumulated in compartment 65 through apertures 42. Fan 81 is turned on and off upon actuation of the rocker actuator of the main power switch SW1. Tubes are suitably supported above bottom wall 40 to accommodate fan 81. Fan 81 may be a mini Delta fan, such as Model DFD0412LL, or the equivalent, having 11-
35 13.8V DC and 0.05 amp rating. The ceramic oven, in

-17-

the form of tube 52, as stated above is open at both ends, accommodating hand held placement for drying, exposure to anti-microbial heat, and heat shrinking procedures, yet to be explained herein in greater detail.

It is to be appreciated that the liquid bath within the basin 90 is removed, from time-to-time as appropriate, using equipment available in the hospital, medical and dental offices where the apparatus 20 may be located. For example, the dental oral suction system may be used. Such removal of the disinfecting liquid bath from the basin 90 provides the further benefit of disinfecting and cleaning the suction line, the collection bottle, and the suctioning system itself. Paper towels may be used to wipe residual liquid from the interior surface of the basin after the bath has been aspirated. A 5% hypochlorite or a 5% bleach solution may be used to wipe any iodine or other stains from the surface of the basin 90 and from surrounding regions.

The ceramic tubes 52 and 60 are preferably molded of the highest quality "dinnerware" grade porcelain, fired at 2,000 degrees fahrenheit, which is then glazed both inside and out with a "dinnerware" porcelain glaze and again fired at 2,000 degrees fahrenheit. The resulting porcelain tubes are highly di-electric, non-staining, good heat insulators, and very easy to clean and disinfect with minimal effort. It is preferred that the material comprising the connector 61 (Figure 7) be a suitable high temperature ceramic sealant.

The apparatus 20 will be accompanied by a supply of medical or surgical gloves, to be used by each health-care provider in an appropriate manner. Housing comprising base 24 and lids 26 and 28

-18-

accommodate silk-screening by which various forms of information can be applied thereto.

5 The hot air delivery tube 60 contains heating coils through which air delivered through vents under the displacement force of the fan 78 flows. The amount of heat imparted to the flow of air by the heating coils may be selectively set, as hereinafter more fully explained.

10 The exhaust baffle 55 is best illustrated in Figures 3 and 8. The exhaust baffle (which functions as air diverter and heat shield to prevent injury and damage) comprises a hollow box-shaped configuration comprising a circular air influent opening 120 and a rectangular effluent chimney opening 122, which is
15 illustrated as being covered by a filter 124. See Figure 8. The diameter of the circular influent opening 120 is sized so as to accommodate a manually removable press-fit union over the exposed discharge end 56 of the heating chamber tube 52. The user has
20 the option of facilely utilizing the exhaust baffle 55 or not, as conditions may dictate.

The exhaust baffle 55 comprises solid informally thick side walls 126 and 128, a solid rear wall 130, each of uniform thickness, and formed as one piece.
25 Baffle 55 also comprises a front wall 132 apertured at influent opening 120. Wall 132 is of uniform thickness and parallel to while offset from solid back wall 130. Wall 132 is integral with side walls 126 and 128. The exhaust baffle 55 also comprises a
30 bottom wall 134, one piece with wall 132, of uniform thickness, disposed parallel to the plane containing exhaust opening 122. A short diagonal wall segment 136 joins as one piece side wall 128 and bottom wall 134. The upper edge 138 adjacent exhaust opening 122
35 is disposed within a horizontal plane. The filter 128

-19-

may be adhesively secured at its periphery to edge 138, the filter 128 functioning to cool the exhaust air, thereby reducing the temperature to a level well below that by which a human being may be injured.

5 The exhaust baffle 55 is preferably formed of a ceramic material which is temperature resistant and externally glazed to accommodate ease of cleaning. It may be formed of the same ceramic material from which tubes 52 and 60 are formed to simplify manufacturing.
10 It is preferred that the volume within the hollow interior 140 of the exhaust diverter 55 be large enough to slow the laminar flow of hot air issuing from tube 252 to allow a predetermined dwell time therein, thereby enhancing the cooling function
15 performed by the exhaust baffle 55.

 The base 24 and the lids 26 and 28 are illustrated as being contoured, the top and sides being tapered.

 The paper towels 67 are folded.

20 Reference is now made to Figures 9 and 10 which illustrate one of the handpiece-receiving sheaths 71, shown in flat full-sized condition prior to and after being heat shrunk upon a handpiece 112, respectively. The sheath 71 comprises a thin-wall initially flat bag
25 150 of medical grade synthetic resinous material which is heat shrinkable with two pleats 151 for ease of storage. The bag or sleeve 150 is nevertheless illustrated as being longitudinally seamless along its entire length. The bag 150 is open for receipt of a
30 handpiece at one end 152. End 154 of the sleeve or bag 150 is closed. While any suitable form of closure is satisfactory, in the illustrated embodiment end 154 is closed by a heat seal seam 156. As illustrated in Figure 9, the bag 150 is shown in a collapsed, flat
35 position.

-20-

The bag 150 comprises two longitudinally-directed weakened lines 158, in the form of spaced perforations, the perforations penetrating the wall comprising the bag 150 along two superimposed lines, the top line 158 being illustrated in Figure 9. Thus, the bag 150 comprises a longitudinally directed edge ribbon comprising a distal ribbon portion 160 and a central and proximal ribbon portion 162. The two ribbon portions 160 and 162 are aligned one with the other. The two ribbon portions 160 and 162 are, prior to use, subdivided one from the other by a circumferential or transversely disposed weakened line 164 comprising spaced perforations which penetrate the wall comprising the bag 150 around the full 360 degree circumference of the bag. The aligned longitudinally directed ribbon portions 160 and 162 respectively terminate in a distal tab 166 and a proximal tab 168.

As explained herein in greater detail, the tab 166 accommodates manual grasping and tearing longitudinally along the perforations 160 to transverse perforations 164 and thence transversely along perforations or weakened line 164 to remove ribbon portion 160 and bag or sleeve segment 170 from the handpiece, after the bag has been heat shrunk thereon. This accommodates exposure of the distal end of the handpiece for placement of a burr or other such structure, while continuing to sheath the handle portion of the handpiece still encapsulated by sheath segment 172. This prevents communication of contamination from the hands or gloves of the instrument user to the handle of the handpiece and vice versa.

When use of the handpiece is over and the handpiece is ready for anti-microbial treatment, the remaining segment 172 of the bag 150 is removed by

-21-

grasping tab 168 and pulling it along weakened line 158 to the end of bag segment 172, following which the bag segment 172 and the ribbon 162 are discarded.

5 The heat shrinkable material from which the sheath 71 is fabricated may be 1.25 mil., 60% shrink tubing formed of medical grade polyvinylchloride if desired. One or both of the sheath segments 170 and 172 may be color coded. For example, segment 170 may comprise a blue pigment, with segment 172 transparent, 10 to facilitate visual identification of the location of transverse tear line 164 and to provide visual certainty as to the portion of the bag 150 to be removed to expose the distal end of the handpiece. The bag, once positioned and heat shrunk upon the 15 handpiece, and prior to removal of any portion thereof, provides for open atmospherically or ambiently exposed storage following anti-microbial treatment wherein the handpiece is not subjected to air contamination while being so stored.

20 The disposable heat shrink tube sheath 71, with proximal and distal pull tabs aligned with longitudinal perforations 158, provides an inexpensive and yet effective disposable protection for medical and dental instruments which have been subjected to 25 anti-microbial treatment and a convenient way for hospital, dental offices, and medical offices to non-contaminately handle such instruments conveniently and without extensive technical training or significant risks to the patient. Thus, the heat shrunk sheath 71 30 upon an instrument or handpiece provides a barrier which reduces or eliminates deposition of aerosol fall-out contamination on the handpiece. During use, the heat shrunk sheath 71 resists and reduces transmittal of contamination between the handpiece and 35 the user. The shrunken nature of the sheath 71, with

-22-

bag segment 172 remaining on the handpiece is skin-tight and, therefore, does not alter the tactile feel or control of the handpiece, as used by the health-care provider.

5 The apparatus 20 is capable of being hand carried to the desired location in a hospital, dental office, or medical office and placed upon an appropriate flat surface, such as a countertop. A conventional electrical cord, at one end, is plugged into a wall
10 socket and attached to the electrical receptacle 38 of the apparatus 20 at the other end.

 The outside hinged lid 26 is moved from its closed clamshell position (Figure 1) to an open position (Figure 4) and the basin cover 102 is removed
15 from within the basin 90.

 A suitable diluted disinfecting solution is placed in the basin 90 up to the inscribed line 95 to provide the proper volume of anti-microbial liquid
20 comprises a bath contained within the basin 90.

 Any number of disinfectants may be used in a proper diluted form to comprise the bath within the basin 90. For example, iodophor/nonoxynol-9 marketed as "Multi-Wash" by Gull Laboratories, Inc. of Salt Lake City, Utah, which is an anhydrous liquid mixture
25 consisting chiefly of monononylphenyl ethers of polyethylene glycols in complex with iodine, may be used. Any suitable EPA registered disinfectant may be used.

 To the extent advisable, the distal end and the
30 part of the handle earlier immersed within the bath contained in basin 9 are subjected to rinsing, by any suitable liquid, such as distilled water. Only some disinfectants require a rinsing cycle following removal from the bath. Others do not.
35 Iodophor/nonoxynol-9 (Multi-Wash) requires no rinse.

-23-

One way of providing a suitable, easily handled system for dilution of a concentrated disinfectant is to provide a predetermined amount of concentrated disinfectant in a small container, adequate to provide an appropriate diluted quantity when mixed with one gallon of distilled or other suitable water. By providing a gallon container of suitable water, with sufficient air volume at the top to receive all of the concentrated disinfectant from the smaller container, the contents of the smaller container are simply poured into the large container, which is then recapped and oscillated until a uniform mixture is obtained. From the diluted disinfectant in the one gallon container, the basin 90 may be filled more than once. Where the iodophor/nonoxynol-9 disinfectant is used, and 1.2 fluid ounces of the Multi-Wash concentrate is added to one gallon of distilled water, the result is a a-(p-Nonylphenyl)-w hydroxypoly-(oxyethylene)-Iodine complex of 150ppm Iodine dilution.

While distilled water is preferred, the iodophor/nonoxynol-9 diluted solution mentioned above is unaffected by water hardness up to at least 150 ppm CaCO_3 and, therefore, can be diluted in tap water.

It is recommended that the resulting diluted solution be allowed to set in the basin 90 for a time sufficient to warm to room temperature and to de-aerate, which may take approximately one hour before the bath within the basin 90 should be used initially.

Periodically, the anti-microbial value of the bath within the basin 90 should be checked. A pHyrion micro-IODINE test tape may be used. This product is available from Micro Essential Laboratory of Brooklyn, New York.

-24-

Once the sanitizing liquid comprising the bath within basin 90 is ready for use, the soiled distal end of a medical instrument, such as a dental handpiece 71, and part of the handle thereof is placed
5 in the bath, as illustrated in Figure 5. While not mandatory, the air and water tubes associated with operation of the handpiece 112 may be left in their connected condition as the distal end and part of the handle of the handpiece 112 is allowed to soak. This
10 type of soaking after use prevents the overburden or debris on the instrument from drying, among other things.

With at least one handpiece 112 in its soaking position as illustrated in Figure 5, the operator
15 actuates the main power switch SW1 to communicate electrical energy to the circuits of the apparatus 20, which circuits are yet to be described. Thereafter, the operator of the apparatus 20, with a used handpiece 112 soaking in the bath of basin 90,
20 actuates the membrane switch SW2 which delivers electrical energy to the ultrasonic transducer TR1 (Figure 6), thereby dissipating ultrasonic energy or waves through the bath and across the instrument 112. By subjecting the bath and the handpiece 112 to
25 ultrasonic waves causes the debris or overburden to be removed from the handpiece 112 and assists the disinfectant within the bath to reach most if not all surface areas of the portion of the handpiece 112 immersed within the bath. While not mandatory in
30 accordance with the principles of the present invention, a timing circuit is provided which limits the length of time to which the bath and the handpiece 112 are subjected to the ultrasonic energy emitted by transducer TR1.

-25-

Caution should be taken so that the ultrasound transducer is not operated when the basin 90 is empty.

If the potency of the diluted disinfectant within basin 90 falls below a predetermined amount, the bath
5 should be aspirated, and appropriately replaced, as explained above.

When the soaking, anti-microbial bathing, and ultrasonic steps have been completed, the basin lid 102 is lifted and the handpiece 112 removed, after
10 which the lid 102 is returned to its in-basin position.

It is always advisable to actuate the handpiece after being removed from the bath contained within basin 90 so as to drive air and liquid cleaning
15 solution through the handpiece from the supply hoses attached at the proximal thereof. The air/water discharge may be directed into a towel to prevent discharge of airborne pollution. This will remove any residual debris and other sources of contamination as
20 well as bath solution from the interior passageways at the distal end of the handpiece 112.

In any event, after removal from the bath where no rinsing is required or after rinsing where required, a paper towel is preferably removed from the
25 stack 67 of towels and the handpiece is lightly tapped against and air and water operated into the towel, preferably while held in one hand of the operator. The towel may also be used to remove surface liquid from the handpiece.

30 Holding the handpiece 112 in one hand, the operator next inserts substantially all, except for the proximal end being held in the hand, into the anti-microbial heat chamber 50 and actuates membrane switch SW3. Anti-microbial heat, at an appropriate
35 temperature of typically 750 degrees fahrenheit or

-26-

more, is delivered from the heating coils contained within tube 60, by operation of the fan 78, resulting in laminar flow through the interior of the tube 52, which both dries residual liquid on the handpiece 112 and subjects the handpiece to anti-microbial heat. A temperature of about 750 degrees farenheit or higher is appropriate. Normally a timed interval of about 15 seconds is satisfactory, although greater lengths of time could be used to enhance the anti-microbial effectiveness. Repeat anti-microbial heat cycles may also be used. However, care should be taken to avoid heat damage to the handpiece. The capacity to harmlessly absorb heat varies from handpiece to handpiece. It is preferred that the circuitry of the apparatus 20 comprise a predetermined cycle time for drying and anti-microbial heat exposure, during which time it is recommended that the operator moderately rotate and/or otherwise move the handpiece while it is extended into the tube 52.

In situations where the anti-microbial heat available by reason of one or more cycles of exposure of the handpiece 112 to anti-microbial heat in chamber 50 is deemed insufficient, the air and water hoses may be removed from the handpiece 112 and the handpiece can be subjected to autoclaving.

The fingers of the operator are not to be inserted into the ultrasound tank nor into the ceramic tube 52 during operation.

After removal of the handpiece 112 from the anti-microbial heat chamber 50 or, in the alternative, after autoclaving where autoclaving is used, the anti-microbially treated handpiece is placed through the open distal end 152 of one of the sheaths 71. While the handpiece may be inserted up to seam 156, it is preferred presently that the handpiece be left spaced

-27-

a short distance from the seam 156 to accommodate shrinkage.

5 The sheathed handpiece is next manually placed within and manually held within the chamber 50 defined by tube 52. The heat shrink switch SW4 is actuated and the sheathed handpiece rotated and/or otherwise moved moderately within the chamber 50 as the sheath is heat shrunk. The actuation of switch SW4 subjects the sheath to a heat shrinking temperature of
10 approximately 450 degrees fahrenheit for an interval of approximately twelve or more seconds. If desired, a suitable lubricant can be applied to the handpiece prior to placement in the sheath 71 or after removal of sheath segment 170.

15 When the heat shrinking cycle is over, the encapsulated handpiece is manually removed from the chamber 50 with the sheath shrunk into snug contiguous conforming relation with the handpiece. When use of the apparatus 20 has been completed, the main power
20 switch SW1 is shut off at its rocker actuator exposed at the left side of the base 24. The closed distal end 154 shrouds the distal end of the handpiece. While it is preferred that the length of the sheath 71 be such as to cover the distal end and the entire
25 handle of the handpiece, the present invention is broad enough to include coverage of the distal end only or the distal end and a part of the handle of the handpiece 112.

30 The contiguously encapsulated sheathed handpiece is thereafter stored in an open condition in a desired storage place in the hospital, the doctor's office, or the dental office. The contiguous sheath prevents air-borne contamination of the encapsulated handpiece.

35 At the time of use, the health-care provider lifts the sheathed handpiece from its storage location and,

-28-

if not already connected, the air and water hoses are connected at the proximal end of the handpiece.

5 The distal segment 170 of the heat shrunk sheath 71 is manually removed by grasping distal tab 166 and tearing first along weakened line 158 to weakened line 164 and thence along weakened line 164 away from line 158 until segment 170 has been severed from the handpiece. Segment 170 and ribbon portion 160 are then discarded. The burr or other distal workpiece
10 instrumentation of the handpiece is added. The health-care provider grasps the handle of the handpiece through the heat shrunk sheath segment 172 as the handpiece is used with the patient.

15 When use of the handpiece has been completed, the distal tab 168 is manually grasped and the sheath segment 172 is removed by tearing the ribbon 162 from the sheath segment 172 along weakened line 158. Both the ribbon 162 and the segment 172 are then discarded.

20 The handpiece is returned to its soaking position in the disinfecting bath contained within basin 90 and the process is repeated.

25 It is to be appreciated that the tool or instrumentation fixed during use to the distal end of the handpiece is normally removed after use and is separately cleansed and anti-microbially treated prior to subsequent use, or discarded if disposable.

30 Use of surgical or like gloves is recommended during both the use of the handpiece 112 and during handling of the handpiece as it is soaked, cleaned, and anti-microbial treated. Re-gloving is recommended when the gloves either become contaminated or are in some way damaged during use.

35 Reference is now made to Figure 11 which is the main wiring diagram by which electrical power is distributed to specific circuits comprising part of

-29-

the apparatus 20. Conventional 110 v, 60 cycle AC electrical power is communicated, as mentioned above, to three pronged receptacle 38. One terminal 200 of receptacle 38 is at ground potential. Another
5 terminal 204 is neutral, while terminal 202 is hot.

When the main power or master switch SW1 is off, the apparatus 20 is starved for power. When switch SW1 is manually displaced to its on position, power is communicated from terminal 202 of receptacle 38 along
10 conductor L2, across 15 amp circuit breaker 36 and closed switch SW1 and along conductor L4 to terminal 1 of distribution strip 206. Circuit breaker 36 may be an E-T-A series 1658-P10 or equivalent. Terminal block or strip 206 may be a Wieland Euro-style eight-
15 position terminal block. The power input at terminal 1 of strip 206 is communicated across terminals 9, 10, 11, 2, and 3 of strip 206 to conductors L6 and L8. Conductor L6 supplies electrical power to the heating coils in tube 60. Power communicated along conductor
20 L8 across 5 amp circuit breaker 34, which may also be an E-T-A series 1658-P10 or equivalent, to terminal 1 of distribution strip 208. This power is output from terminals 3 and 4 of strip 208 to the motherboard circuit and the ultrasonic circuits, respectively.

25 Terminal 204 of receptacle 38 is connected by conductor L10 to terminal 12 of strip 206, thereby placing terminals 4, 5, 6, 13, and 14 and conductors L12, L14, and L16 at neutral.

Ground terminal 200 of receptacle 38 is connected
30 to and grounds terminals 7 and 8 of strip 206. The ground for the heating coils in tube 60 and the ground for the ultrasound circuit are respectively ground at terminals 16 and 15.

Reference is now made to Figure 12, which
35 illustrates the motherboard low voltage, DC power

-30-

circuit, generally designated 220. Conventional 110 VAC power is tapped from the wiring diagram 198 of Figure 11 and applied to the high voltage side of transformer TR1, which is a conventional 110 VAC to 12.6 VAC, 500m amp transformer. The transformer TR1 thus provides a low 12.6 volts AC output to bridge rectifier BR1. Rectifier BR1 may be a 1 amp, 50 PIV rectifier, one side of which is at ground. The 12.6 volts DC output from rectifier BR1 is communicated to the 12 volt circuits, yet to be described, across fixed voltage regulator 222, which has a 12V DC 1 amp output.

Element C1 is a 470 micro-farad capacitor which serves to flatten the 60 HzDC issuing from the AC transformer TR1 through the bridge rectifier R1 to the voltage regulator 222. The 22 micro-farad capacitor C2 serves to flatten out and remove any high frequency noise which occurs in the +12V DC power supply.

Reference is now made to Figure 13, which illustrates the heat/blower control circuit, generally designated 234. The 110 VAC power supply is communicated at one side to the fan 78 and the heating coils within tube 60 and at the other side to relay RE1. Relay RE1 is normally open, which starves the fan 78 and the heating coils for power until relay RE1 becomes conductive, as explained below.

The +12V DC power supply is communicated to circuits 235 and 233, either of which can energize the coil of relay RE1. The positive end of the coil is connected to terminal 1 of relay RE1, while terminal 2 is at ground potential.

The +12V DC power supply is connected directly to terminals 14 of integrated timing circuits 227 and 229 and across variable resistors VR1 and VR2 to terminals 1 and 2 of integrated circuits 227 and 229. The +12V

-31-

DC power supply is also connected respectively across resistors R2 and R4 to terminal 6 of circuits 227 and 229.

5 Terminal 7 of each of circuits 227 and 229 is at ground potential. Capacitors C5 and C8 respectively connect at one side thereof to terminal 3 of circuits 227 and 229, with the other side at ground.

10 Integrated circuits 227 is a first integrated circuit 236 (Figure 14) which component may be part no. 511-HE556 available from Signetics. Integrated circuits 229 and 231 are first and second sections of the same component, which component may be part no. 511-HE556.

15 Capacitors C4, C3, and C5 each function to eliminate high and low frequency interference injected into the lines from switches, relays, and outside influences.

20 Resistors R1 and R2 function, respectively, to lower the amperage (to about 1 milliamp) to prolong life of the membrane switch and to reduce voltage to properly operate timer 227.

25 Circuit 235 is activated when switch SW3 is manually actuated. Variable resistor VR1 can be selectively set and functions, when circuit 235 is on, to initially deliver electrical power to terminals 1 and 2 of integrated circuit 227, which triggers circuit 227. The time sequence is lengthened by adjusting variable resistor VR1. Higher resistance yields longer time sequence (adjustable from 0 seconds to +1 hour).

30 After switch SW3 is on and circuit 227 is triggered, the output from circuit 227 at terminal 5 thereof across diode D1 energizes the coil of relay RE1 to a relatively high level thereby completing the circuit to fan 78 and the heating coils in tube 60.

35

-32-

The temperature emanating from the heating coils is relatively high, on the order of 750⁰F or more, thereby producing the above-mentioned anti-microbial heat in chamber 50. Production of this heat continues until
5 timer 227 shuts off at the pre-set time lapse as adjusted and set by variable resistor VR1 during the assembly stage of the circuit. A fixed resistor of the appropriate value may be used in place of variable resistors VR1, VR2, and VR3, however, to do so does
10 not allow fine-tuning the timing sequences.

Capacitors C6, C7, and C8 each functions to remove low frequency and high frequency noise injected by the operation of switches, relays, and even outside influence.

15 Resistors R3 and R4 function, respectively, to reduce amperage at SW4 to prolong membrane switch life and to reduce voltage to proper voltage for operation of timer 229.

Variable resistor VR2 can be selectively set and
20 functions, when circuit 233 is on, to initially deliver electrical power to terminals 1 and 2 of integrated circuit 229, which triggers circuit 229. Variable resistor VR2 performs the same function as variable resistor VR1.

25 After switch SW4 is on and circuit 229 is triggered, the output from circuit 229 at terminal 5 thereof is across resistor R5 and diodes D3 and D2, which energizes the coil of relay RE1 to a relatively low level thereby completing the circuit to fan 78 and
30 the heating coils in tube 60. The temperature emanating from the heating coils is relatively low, on the order of 450⁰F, thereby producing the above-mentioned heat shrink temperature in chamber 50. Production of this heat continues until timer 229
35 shuts off.

-33-

The output from terminal 5 of timer 229 is also communicated across diode D4 to the collector of transistor Q1. The +12V DC power is also supplied across resistor R6. The base of transistor Q1 is made
5 conductive by power supplied across resistor R7 from terminal 9 of timer 231. Once the transistor Q1 is conductive, it discharges to ground at the emitter thereof. This reduces the power level communicated to terminal 1 of relay RE1 from timer 229.

10 One side of capacitor C9 is connected to terminal 11 of timer 231, with the other side being at ground.

The +12V DC power supply is communicated across resistor R9 to terminal 13 of timer 231 and thence across variable resistor VR3 to terminals 12 and 8 of
15 timer 231, which terminals also connect to one side of capacitor C10, the other side of which is at ground.

Resistor R5 is current limiting and serves to reduce voltage to three volts, while resistor R6 functions in the same way.

20 The purpose of each of the resistors R7 and R8 is to reduce the voltage to less than one volt to be compatible with the transistor Q1.

Resistor R9 serves to divide the on and off time cycle for variable resistor V3 while variable resistor
25 VR3 performs the function of controlling the division or percentage of power reaching related terminals of timer 231.

Diodes D1 and D2 function collectively as an OR gate. Diode D1 works when the anti-microbial heat
30 cycle is on. Diode D2 works during the heat shrink cycle. Diodes D3 and D4 each serves to combine signals to control timer and power percentage.

Capacitors C9 and C10 respectively removes oscillation and, in conjunction with resistor R9 and
35 variable resistor VR3 to control percentage of power.

-34-

Transistor Q1 is a phase converter.

Reference is now made to Figure 14, which illustrates an ultrasound timing circuit, generally designated 238. The 110 VAC power supply is communicated to circuit 238 so that hot conductor is connected to a conventional ultrasound generator circuit 236' and ground is connected to terminal 1 of relay RE2. Thus, relay RE2 functions as a switch and must be turned on before ultrasound generator circuit 236 is energized. When RE2 is turned on, ultrasound generator circuit delivers power to transducer TR1 causing emission therefrom of ultrasonic vibrations as explained above. Relay RE2 may be a 100V, 2 amp relay with a 12V, 30 micro amp coil, such as part 431-1212. Circuit 236 may be a 556 DIP, 14 dual timer, part no. 511-NE-556.

The coil of relay RE2 is turned on by integrating timing component 236, terminal 9 of timer 236 being connected to the positive side of the coil at terminal 2 of relay RE2. The negative side of the coil, at terminal 3 of relay RE2, is at ground potential.

The +12V DC power supply is communicated along conductor L20 to terminal 14 of timer 236, across fine tuning variable resistor VR4 to terminals 12 and 13 of timer 236 and across resistor R11 to terminal 8 of timer 236. Terminal 7 of timer 236 is at ground potential, while terminal 3 is connected to one side of capacitor C13, the other side of which is at ground potential. The timer 236 is triggered upon manual closing of ultrasonic switch SW2 (with the main power switch SW1 on).

Resistor R10 serves to drop current (amperage to 1 milliamp) at switch SW2 to prolong the membrane switch cycle life, while resistor R11 functions to

-35-

drop voltage to correct operating voltage supply to terminal 8 on timer 236.

Capacitor 12 serves to remove both low and high interference signals from the line caused by switches and other electronic devices, while the purpose of capacitor C13 is to remove both high and low frequency interference in ground line from relay RE2 and other outside influences.

Potentiometer or variable resistor VR4 is adjustable, the resistance of which increases with time so that at a predetermined time timer 236 is starved for power thereby turning relay RE2 off.

Reference is now made to Figure 15, which illustrates an over-heat control circuit, generally designated 240, preferably mounted on a motherboard. The +12V DC power supply from circuit 220 is communicated to the input of circuit 240. Thermistor T1, located on the exterior of tube 52, is normally closed, but opens when the main power switch SW1 is on and either switch SW3 or SW4 has been actuated and the external temperature of tube 52 has reached a predetermined magnitude. Thermistor 71 may be a 3/4" bi-metal disk relay with an automatic reset feature.

Opening of thermistor T1 turns hot air fan or blower 78 on, thereby driving air from tube 60 through heating chamber tube 52.

Relay RE3 functions to open the 12V DC lines to shut down communication of the DC power to the relays RE1 and RE2 (see Figures 13 and 14), and closes the line to fan 78 until such time as the temperature in the compartment 65 falls below 130°F. When the temperature in compartment 65 falls below 130°F, the Thermistor T1 automatically resets, which shuts down and re-closes the circuit by which DC power is provided.

-36-

The invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiment is, therefore, to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

What is claimed and desired to be secured by Letters Patent is:

-37-

Claims:

1. An anti-contamination sheath for a medical or dental handpiece comprising a flexible bag comprising a thin wall of synthetic resinous material closed at one end and opened at another end, the bag comprising perforations in the wall accommodating manual tearing of the bag along the perforations to accommodate removal of at least part of the bag from the handpiece.
2. A sheath according to Claim 1 wherein the synthetic resinous material comprises a heat shrinkage film plastic.
3. A sheath according to Claim 1 wherein at least some of the perforations are aligned and longitudinally directed.
4. A sheath according to Claim 1 further comprising a tab located at least one end of the bag, the tab and the bag being formed as one piece from the same synthetic resinous material.
5. A sheath according to Claim 4 wherein the tab is generally aligned with at least some of the perforations.
6. A sheath according to Claim 1 further comprising two tabs, respectively disposed at the two ends of the sheath.

-38-

7. A sheath according to Claim 1 wherein some perforations are longitudinally aligned and others are transversely aligned creating bag segments which can be individually selectively manually removed to expose
5 a distal end and a main body of the handpiece, respectively.

8. A sheath according to Claim 7 wherein at least one bag segment is color coded.

9. A sheath according to Claim 7 further comprising a tab disposed at least one end of the bag aligned generally with the longitudinal perforations.
10

10. A sheath according to Claim 1 wherein at least a portion of the bag is transparent.

11. An anti-contamination sheath for dental and
15 medical handpieces comprising a thin wall elongated pliant sleeve of heat shrinkage synthetic resinous material into which one handpiece is manually placed comprising at least one weakened line accommodating manual tearing of the material after being heat shrunk
20 upon the handpiece along the weakened line for removal of at least part of the bag from the handpiece.

12. A sheath according to Claim 11 wherein the material of the bag comprises at least two weakened lines to accommodate separate manual removal of two
25 segments of the bag from the handpiece.

13. A sheath according to Claim 11 which is creased longitudinally to form two parallel edges during storage, but accommodating placement therein of the handpiece through an open end of the sheath.

-39-

14. A sheath according to Claim 11 wherein the sheath is closed at one end.

15. A sheath according to Claim 11 further comprising at least one exposed pull tab juxtaposed the weakened line.

16. In combination handpiece and an anti-contamination sheath contiguously encapsulating a distal end and a main body of the handpiece, the sheath comprising a pliant bag comprising a thin wall of heat shrunk synthetic resinous material closed at one end, the material of the bag comprising at least one weakened wall portion accommodating manual tearing of the wall along the weakened wall portion for removal of at least part of the bag from the handpiece.

17. The combination of Claim 16 wherein the wall of the bag comprises at least two weakened lines to accommodate selective independent manual removal of two segments of the bag from the handpiece.

-40-

18. A unitary anti-microbial apparatus comprising:

- 5 (a) a basin for soaking a distal end and at least part of a handle portion of a used handpiece in liquid to (1) prevent drying of debris derived from use in an oral cavity of a patient, and (2) for exposure of the immersed parts of the handpiece to an anti-microbial agent in the liquid;
- 10 (b) a source of ultrasonic waves associated with the basin for removing the debris and enhance the disinfection;
- 15 (c) a heat chamber accommodating receipt of the distal end and the at least part of the handle of the handpiece after removal thereof from the basin to (1) dry, (2) expose the same to anti-microbial heat, and (3) to accommodate heat shrinking of a plastic sheath contiguously upon and around the distal end and at least some
- 20 portion of the handle of the handpiece.

19. The unitary anti-microbial apparatus according to Claim 18 further comprising a supply of plastic sheaths.

25 20. The unitary anti-microbial apparatus according to Claim 19 wherein each sheath is heat shrinkable and closed at one end.

21. The unitary anti-microbial apparatus according to Claim 18 further comprising a supply of disposable towels.

-41-

22. The unitary anti-microbial apparatus according to Claim 18 further comprising controls and circuitry for the ultrasonic and the heat chamber for anti-microbial and heat shrink purposes.

5 23. The unitary anti-microbial apparatus according to Claim 18 wherein the heat chamber comprises a tube into which the handpiece is manually inserted and manually held for anti-microbial and heat shrink purposes.

10 24. The unitary anti-microbial apparatus according to Claim 18, the apparatus comprising a housing comprising a base and at least one cover.

15 25. The unitary anti-microbial apparatus according to Claim 24 wherein the base and cover are connected by a hinge.

20 26. The unitary anti-microbial apparatus according to Claim 18 wherein the basin comprises a removable lid with at least one opening therein through which the handpiece may be inserted into the liquid in the basin.

25 27. The unitary anti-microbial apparatus according to Claim 18 wherein the heat chamber comprises an exhaust site, the apparatus further comprising an exhaust baffle juxtaposed the exhaust site to inconsequentially dissipate the exhaust.

-42-

28. The unitary anti-microbial apparatus according to Claim 18 wherein a heat source is juxtaposed the heat chamber such that hot air is caused to flow through the heat chamber as laminar flow.

29. The unitary anti-microbial apparatus according to Claim 18 further comprising surgical type rubber gloves.

30. The unitary anti-microbial apparatus according to Claim 18 wherein the heat chamber comprises glazed heat resistant material.

31. The unitary anti-microbial apparatus according to Claim 18 wherein the apparatus comprises a counter-top cabinet.

32. The unitary anti-microbial apparatus according to Claim 18 wherein the apparatus is portable, pumpless, and drainless.

-43-

33. A method of subjecting a handpiece of the dental/medical type to multiple consecutive anti-microbial treatments comprising the steps of:

5 soaking a distal end and at least some of a handle of the handpiece in liquid after use;

immersing the distal end and at least a portion of the handle of the handpiece in the anti-microbial liquid agent;

10 subjecting the distal end and at least part of the handle of the handpiece immersed in liquid to ultrasonic waves;

exposing the distal end and a length of the handle of the handpiece to anti-microbial heat for a predetermined period of time;

15 removing the handpiece from the anti-microbial heat and thereafter encapsulating the distal end and at least some of the handle of the handle piece in a pliant sheath of synthetic resinous film material;

20 heat shrinking the sheath into snug contiguous relation with the handpiece;

removing the heat shrunk sheath and handpiece from the heat; and storing the sheathed handpiece for later use.

25 34. A method according to Claim 33 further comprising the steps of removing and discarding at least a portion of the heat shrunk sheath from around the distal end of the handpiece and thereafter orally using the handpiece.

-44-

35. A method according to Claim 33 further comprising the steps of removing and discarding a first portion of the heat shrunk sheath from around the distal end of the handpiece leaving a second
5 portion of the heat shrunk sheath around the handle of the handpiece, manually gripping the handle through the second portion of the heat shrunk sheath while orally using the handpiece, removing and discarding the second portion of heat shrunk sheath from the
10 handle and thereafter again repeating the steps of Claim 33.

36. A method according to Claim 33 wherein the exposing step is performed while a proximal end of the handpiece is hand held.

15 37. A method according to Claim 33 wherein the heat shrinking step is performed while a proximal end of the handpiece is hand held.

38. A method according to Claim 33 wherein the soaking, subjecting, and immersing steps are practiced
20 in a common bath.

39. A method according to Claim 33 wherein the exposing and heat shrinking steps take place at the same location.

40. A method according to Claim 33 wherein the
25 soaking step is preceded by creating a liquid bath comprising an anti-microbial agent and thereafter performing the soaking, subjecting, and immersing steps therein.

-45-

41. A method according to Claim 40 wherein the soaking, subjecting, and immersing steps are practiced below a removable lid disposed over the bath.

5 42. A method according to Claim 41 wherein the proximal end of the handpiece extends above the bath through an opening in the lid as the soaking, subjecting, and immersing are performed.

10 43. A method according to Claim 33 where liquid is manually removed from the handpiece after the immersing step and prior to the exposing step.

44. A method according to Claim 33 further comprising aspirating spent liquid used in performing at least one of the soaking, subjecting, and immersing steps through a dental suction tube.

15 45. A method according to Claim 33 further comprising manually manipulating controls to accommodate the subjecting, exposing, and heat shrinking steps.

20 46. A method according to Claim 33 wherein the removing step comprises manually severing at least a portion of the heat shrunk sheath along a weakened tear line.

25 47. A method according to Claim 35 wherein each removing step comprises manually severing said first and second portions of the heat shrunk sheath along weakened tear lines.

-46-

48. A method according to Claim 33 wherein the exposing and heat shrinking steps are performed in a hollow, heat-insulated heat chamber.

5 49. A method according to Claim 33 wherein the handpiece is manually displaced during the exposing and heat shrinking steps.

10 50. A method according to Claim 33 wherein the heat shrinking step causes substantially all of the handpiece to be contiguously encapsulated within the sheath.

51. A method according to Claim 33 wherein the exposing step comprises causing hot air of a predetermined temperature to be displaced as laminar flow along a confined chamber.

15 52. A method according to Claim 33 comprising the further step of rinsing the distal end and a segment of the handle of the handpiece prior to the exposing step.

20 53. A method according to Claim 33 wherein the soaking, immersing, and subjecting steps are performed with the handpiece connected for normal operation.

25 54. A method according to Claim 53 comprising the further step of displacing one or more actuator fluids through the handpiece immediately prior to the exposing step.

-47-

55. A method according to Claim 53 comprising the further step of disconnecting the handpiece from its normal operational connection after the subjecting step.

5 56. A method according to Claim 33 further comprising the step of lubricating the handpiece prior to the heat shrinking step.

10 57. A method according to Claim 33 wherein the soaking, immersing, and subjecting steps are performed in a drainless liquid bath of predetermined quantity and comprising the further step of vacuum aspirating all liquid comprising the liquid.

15 58. A method according to Claim 33 comprising the step of creating a liquid bath of predetermined quantity by mixing a concentrated disinfectant with water of a known quantity.

20 59. A method according to Claim 57 wherein the mixing step comprises combining the concentrated disinfectant with a container of water and placing a known amount of the mixing in a basin.

25 60. A method according to Claim 33 wherein the soaking, immersing, and subjecting steps are performed in a drainless anti-microbial bath and comprising the step of selectively testing the bath to determine its anti-microbial strength.

61. A method according to Claim 33 wherein the exposing step comprises subjecting the entire handpiece to anti-microbial treatment.

-48-

62. A method according to Claim 33 wherein the exposing step comprises first drying the handpiece at one site and then subjecting the entire handpiece to anti-microbial treatment at another site.

5 63. A method according to Claim 33 wherein the exposing and heat shrinking steps are performed at the same site.

10 64. A method according to Claim 33 wherein the same site comprises a relatively small continuously open heat chamber.

65. A method according to Claim 33 wherein the same site comprises an elongated tubular heat chamber.

15 66. A method according to Claim 33 comprising a further step of selectively setting different temperatures at the same site for the exposing and heat shrinking steps, respectively.

20 67. An anti-contamination method for a handpiece used upon the human body comprising the steps of:
subjecting the handpiece to at least one anti-microbial treatment;

placing the treated handpiece through an opening in a heat shrinkable sheath closed at one end;
heat shrinking the sheath into snug contiguous encapsulating relation with the distal end and at least part of a handle portion of the handpiece;
25 storing the handpiece in an atmospherically exposed environment for a period of time whereby the encapsulated handpiece remains free from contamination.

-49-

68. A method according to Claim 67 comprising the further steps of:

removing and discarding at least some of the sheath at least from the distal end of the handpiece
5 immediately prior to use.

69. A method according to Claim 67 comprising the further steps of:

removing and discarding only a portion of the sheath encapsulating the distal end of the handpiece;
10 grasping the handle portion of the handpiece through a remainder of the sheath;
using the handpiece;
following the using step, removing and discarding the remainder of the sheath;
15 subjecting the fully unsheathed and used handpiece to at least one anti-microbial treatment.

70. A method of administering multiple anti-microbial treatments to a handpiece of a dental/medical type between successive uses thereof,
20 comprising the steps of ultrasonically separating debris from the handpiece; exposing at least some of the handpiece to an anti-microbial liquid; applying anti-microbial heat to at least a portion of the handpiece; enveloping at least a part of the handpiece
25 in a plastic sleeve which is substantially impervious to microbials.

-50-



71. A portable anti-microbial apparatus by which
a contaminated handpiece is treated comprising:

a housing;




an ultrasonic and anti-microbial liquid immersion
5 compartment within the housing;

a heat applying compartment within the housing
for selective application of anti-microbial heat and
heat for a plastic shrinkage purpose, respectively,
controls.

1/7



2/7








Fig. 4






Fig. 7




Fig. 10

6/7




Fig. 11




Fig. 12

7/7




Fig. 13




Fig. 14





Fig. 15

INTERNATIONAL SEARCH REPORT

 International application No.
PCT/US94/03799

A. CLASSIFICATION OF SUBJECT MATTER IPC(5) : A61C 1/02, 1/16 US CL : 433/104, 116 According to International Patent Classification (IPC) or to both national classification and IPC														
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 206/363, 364, 368, 369, 438, 439, 635; 422/20, 28, 292, 300, 307; 433/32, 104, 116; 604/163, 171, 263 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) NONE														
C. DOCUMENTS CONSIDERED TO BE RELEVANT														
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.												
X ---	US, A, 2,997,043, (FLYNN), 22 August 1961. See column 1 line 63 to column 2 line 40.	1, 14, 15 -----												
Y		1-5, 10, 13												
Y	US, A, 4,453,936, (CASSOU), 12 June 1984. See column 6, lines 62-66.	1-5, 10												
Y	US, A, 5,217,370, (CRAIG ET AL.), 08 June 1993. See column 3, line 47.	10												
Y	US, A, 4,178,735, (JACKSON), 18 December 1979. See column 2, lines 35-45.	13												
A	GB, A, 2,248,188, (PARKER ET AL.), 01 April 1992. See entire document.	1-71												
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.														
<table border="0"> <tr> <td>* Special categories of cited documents:</td> <td>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"A" document defining the general state of the art which is not considered to be part of particular relevance</td> <td>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"E" earlier document published on or after the international filing date</td> <td>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"&" document member of the same patent family</td> </tr> <tr> <td>"U" document referring to an oral disclosure, use, exhibition or other means</td> <td></td> </tr> <tr> <td>"I" document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table>			* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	"A" document defining the general state of the art which is not considered to be part of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family	"U" document referring to an oral disclosure, use, exhibition or other means		"I" document published prior to the international filing date but later than the priority date claimed	
* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention													
"A" document defining the general state of the art which is not considered to be part of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone													
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art													
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family													
"U" document referring to an oral disclosure, use, exhibition or other means														
"I" document published prior to the international filing date but later than the priority date claimed														
Date of the actual completion of the international search 02 SEPTEMBER 1994		Date of mailing of the international search report 28 OCT 1994												
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer  CARY O'CONNOR Telephone No. (703) 308-2701												

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US94/03799

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 5,137,689, (CANTRELL), 11 August 1992. See entire document.	1-71
A	US, A, 4,752,444, (BOWEN ET AL.), 21 June 1988. See entire document.	1-71
A	US, A, 4,308,229, (VOIT), 29 December 1981. See entire document.	1-71
A	WO, A, 92/03171, (DELL ET AL.), 05 March 1992. See entire document.	1-71
A	GB, A, 2,251,382, (SHARPE ET AL.), 08 July 1992. See entire document.	1-71